



## PRODUCT SPECIFICATIONS

### PRODUCT

#### SKU/Color Names :

|                    |                 |
|--------------------|-----------------|
| PANZU-01 Berlin    | PANZU-07 Tulum  |
| PANZU-02 Cancun    | PANZU-08 Sydney |
| PANZU-03 Copa      | PANZU-14 Sicily |
| PANZU-04 Amsterdam | PANZU-15 Kyoto  |
| PANZU-05 Venice    | PANZU-16 Oslo   |
| PANZU-06 Dublin    | PANZU-17 Madrid |

#### Construction :

- 3.5mm Rigid Core (Stone and Virgin DOP Composite)
- 1.2mm IXPE attached cushion (No VOCs)
- 5 unique planks per pattern, 10 with a flip

#### Wear Layer :

12mil with Quantum X™ Technology Finish  
(Proposition 65 Compliant)

#### Installation :

- Click, Valinge Locking System
- Float or Glue Down
- 50 LF before transition needed
- Matching Accessories: 3-in-1 Molding, Flush Stair Nose
- Use Polyurethane for wet spaces. Pressure sensitive adhesive is acceptable for other spaces. Please reference our installation instructions for further details or contact [sales@duratousa.com](mailto:sales@duratousa.com)

\*A 50'x50' install requires 10mm expansion space along walls in uncontrolled environments (such as no HVAC).

\*Do not install below 50°F, 24-hr acclimation time.

\* Use a floor mat for office chairs.

### SIZE/PACKAGING

Plank Size : 7" x 48"

Planks/Carton : 12      Sq. Ft./Carton : 28.365

Cartons/Pallet : 50      Sq. Ft./Pallet : 1,418.25

Sq. Ft./Container : 28,365

### FEATURES



ANTI-SCRATCH



WATER RESISTANT



FIRE RESISTANT



PET-FRIENDLY



HEAVY DUTY WEAR



### TEST DATA

ASTM E492-09  
Impact Sound Conduction  
&  
ASTM E90-09  
Airborne Sound Conduction

6" slab, no drop ceiling:  
STC 52 db / IIC 54 db / IIIC 60 db

OSB subfloor with fiberglass and open  
truss using standard resilient channel  
with fastened gypsum board:  
STC 59 db / IIC 50 db / IIIC 61 db

ASTM D2394  
Slip Resistance DCOF  
(Sliding)

Dry: 0.67  
Wet: 0.50

ASTM D1037  
Dynamic Load Limit

1,162 psi

ASTM F970-22  
Static Load Limit

Passes, 0.29mm indent, 250 psi

ASTM F1914-18  
Residual Indentation

Meets or Exceeds, average 0.05mm

ASTM F2199-20  
Dimensional Stability

Meets or Exceeds

ASTM E648  
Critical Radiant Flux

Meets or Exceeds, Class 1 (>1.10)

ASTM F1514-19  
Resistance to Heat

Meets or Exceeds, average  $\Delta E^*$  0.26

ASTM F1515-21  
Resistance to Light

Meets or Exceeds, average  $\Delta E^*$  0.74

ASTM F925-13  
Resistance to Chemicals

No change, Not affected

ASTM E662  
Smoke Density

Meets or Exceeds, <400

### WARRANTY



**LIGHT COMMERCIAL USE**  
Durable enough to withstand  
everyday foot traffic.



**QUANTUM X™ TECHNOLOGY**  
Industry-leading resistance to scratches,  
scuffs and dents, strengthened by  
real titanium.