

PRODUCT

SKU/Color Names :

XL-01 Biscotti	XL-06 Porcini
XL-02 Oat	XL-07 Truffle
XL-03 Sea Salt	XL-08 BonBon
XL-04 Oyster	XL-09 Caramel
XL-05 Maple	XL-10 Mocha

Construction :

- 6mm Rigid Core (Stone and Virgin DOTP Composite) (Single Extrusion Stone Polymer Composite)
- 1mm IXPE attached cushion (No VOCs)
- 8 unique planks per pattern, 16 with a flip

Wear Layer :

20mil with Quantum X[™] Technology Finish (Proposition 65 Compliant)

Installation :

- Click, Valinge Locking System
- Float or Glue Down
- 100 LF before transition needed
- Matching Accessories: 3-in-1 Molding, Stair Tread, Stair Nose, Flush Stair Nose
- Use Polyurethane for wet spaces. Pressure sensitive adhesive is acceptable for other spaces. Please reference our installation instructions for further details or contact sales@duratousa.com

*A 50"x50" install requires 10mm expansion space along walls in uncontrolled environments (such as no HVAC).

* Do not install below -19°F or above +176°F.

* Use a floor mat for office chairs.

SIZE/PACKAGING

Plank Size : 8.97" x 70.86"

Planks/Carion : 4 Sq. Ft./Carion : 17.67

Cartons/Pallet : 52 Sq. Ft./Pallet : 918.84

Sq. Ft./Container : 16,539.12

FEATURES



AUTHTEXT[™] FINISH
High-definition imagery plus an enhanced to Register creates an authentic wood-look and texture.



CLIMATEGUARD[™] RESISTANCE
Resists extreme temperatures, allowing product to be used in 3-season spaces.



LARGE AND LUXURIOUS
Ultra-long and extra-wide planks provide an upscale look, and are 89% larger than standard 7"x48" planks.



QUANTUM X[™] TECHNOLOGY
Industry-leading resistance to scratches, stains and dents, strengthened by real minerals.



HEAVY COMMERCIAL USE
Durable enough to withstand heavy, everyday, foot traffic.

TEST DATA

ASTM E492-09 Impact Sound Conduction &	6", no drop ceiling: STC 52 / IIC 53 / IIIC 55
ASTM E90-09 Airborne Sound Conduction	Open web truss on OSB with gypsum and a drop: STC 61 / IIC 55 / IIIC 62

* Sound test scores are relative to varying conditions. For accurate results, contact Dürato for on-site testing and/or specific buildouts.

ASTM D2394 Slip Resistance DCOF (Sliding)	Dry: 0.64 Wet: 0.51
--	------------------------

ASTM D1037 Dynamic Load Limit	2,200 psi
----------------------------------	-----------

ASTM F970-22 Static Load Limit	Passes, 0.25mm indent, 250 psi
-----------------------------------	--------------------------------

ASTM F1914-18 Residual Indentation	Meets or Exceeds, average 0.03mm
---------------------------------------	----------------------------------

ASTM F2199-20 Dimensional Stability	Meets or Exceeds
--	------------------

ASTM E648 Critical Radiant Flux	Meets or Exceeds, Class 1 (>1.10)
------------------------------------	-----------------------------------

ASTM F1514-19 Resistance to Heat and Cold	Meets or Exceeds, average ΔE^* 0.27
--	---

ASTM F1515-21 Resistance to Light	Meets or Exceeds, average ΔE^* 0.64
--------------------------------------	---

ASTM F925-13 Resistance to Chemicals	No change, Not affected
---	-------------------------

ASTM C518 Thermal Resistance	R Value -0.6
---------------------------------	--------------

WARRANTY

 LIFETIME	 LIFETIME	 LIFETIME	 15 YEAR	 5 YEAR
LIMITED RESIDENTIAL WEAR WARRANTY	LIMITED STRUCTURAL WARRANTY	LIMITED WATERPROOF WARRANTY	LIMITED COMMERCIAL WEAR WARRANTY	LTD ENCLOSED MATS & CABLE WARRANTY